



# LIONSHEAD

## NO EXCUSES Guaranteed!

At Lionshead, we are so confident in the performance of our tires and wheels, we will replace **any ST radial tire** for **any reason** for the first twelve (12) months from date of retail sale.

This guarantee is part of our industry leading,  
**"1•2•5 Lifetime+ Program"**



**1 Year (First Year) "No Excuses Guarantee"**



**2 Year Complimentary Roadside Assistance**  
Owner can use this program to have a service technician come out and remove the damaged assembly and install the inflated spare at any time.



**5 Year Warranty on Radial ST Tires**  
Five year protection from all manufacturer's defects.



**Lifetime Structural Warranty on All Wheels**  
Lifetime protection from all manufacturer's defects on all wheels.



**+ NITRO-FILL in All Tires**  
Nitrogen maintains a tire's proper PSI longer, providing better performance and handling.

### Contact Lionshead Today!



**President: Tim Miller**  
(260) 341-0210  
tmiller@lionsheadtireandwheel.com



**National Sales Manager: Connor Kruggel**  
(719) 640-9801  
ckruggel@lionsheadtireandwheel.com





# LIONSHEAD

## Tire and Wheel Specifications

### Radial Specifications

Size	Ply	Maximum Load (lb)	Pressure
ST145R12 LRD	8	1220	65PSI
ST145R12 LRE	10	1520	80PSI
ST175/80R13 LRC	6	1360	50PSI
ST185/80R13 LRD	8	1710	65PSI
ST205/75R14 LRC	6	1760	50PSI
ST205/75R14 LRD	8	2040	65PSI
ST215/75R14 LRD	8	2200	65PSI
ST205/75R15 LRC	6	1820	50PSI
ST205/75R15 LRD	8	2150	65PSI
ST225/75R15 LRC	6	2150	50PSI
ST225/75R15 LRD	8	2540	65PSI
ST225/75R15 LRE	10	2830	80PSI
ST235/75R15 LRC	6	2340	50PSI
ST235/75R15 LRD	8	2910	65PSI
ST235/80R16 LRE	10	3520	80PSI
ST235/85R16 LRE	10	3640	80PSI
ST235/85R16 LRF	12	3960	95PSI
ST235/80R16 LRG	14	4080	110PSI
ST235/85R16 LRG	14	4400	110PSI
LT225/75R16 LRE	10	2680 single/2470 dual	80PSI
LT235/85R16 LRE	10	3420 single/2778 dual	80PSI
LT235/85R16 LRG	14	3750	110PSI
LT315/70R17 LRD	8	3195 single/2910 dual	50PSI
215/75R17.5 LRH	16	4805 single/4546 dual	123PSI
235/75R17.5 LRH	16	6005 single/5675 dual	128PSI
245/70R19.5 LRG	14	4540 single/4410 dual	110PSI

### Aluminum Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
12x4	5-4.5	1520
13x5	5-4.5	1710
14x5	5-4.5	2040
15x5	5-4.5	1820
15x6	5-4.5	2200
15x6	6-5.5	2830
16x6	6-5.5	3300
16x6	8-6.5	4080
16x6	8-6.5 HD	4400
17.5x6.75	8-6.5 (9/16")	4850
17.5x6.75	8-6.5 (5/8")	6050

### Steel Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
8x7	5-4.5	1075
10x6	5-4.5	1535
12x4	5-4.5	1520
13x4.5	5-4.5	1710
14x5.5	5-4.5	2200
15x5	5-4.5	2150
15x5	5-5	2150
15x6	5-4.5	2200
15x6	5-5	2200
15x6	6-5.5	2830
16x6	6-5.5	3300
16x6	8-6.5	4080
16x6	8-6.5 HD	4400
17.5x6.75	8-6.5 (5/8")	6005